

CONCEPT1

2-zone integrated stereo mixing amplifier



For a long time, installers worldwide have been unhappy with consumer electronics and they were looking for a professional integrated amplifier for use in commercial environments, boardrooms or small businesses designed for 24/7 operation. Therefore Apart developed the CONCEPT1, a stereo or two mono channel (2 x 80 watts @ 4 ohms) amplifier for small and medium-sized projects.

This CONCEPT1 2-zone integrated stereo amplifier can operate with one stereo zone, two volume-linked mono zones or two individual-volume mono zones. The unit can be controlled via RS232 what makes integration into your AV solution possible. The built-in limiters and system design guarantee a failsafe solution 24 hours a day, 7 days a week.

To make the life of the end-user as easy as can be, the CONCEPT1 has user settings and installer settings. Only the absolute necessary features like volume, tone control and source selection can be adjusted by the end-user. The other advanced settings (operation mode settings, maximum music and mic volume, gain input adjustment, automatic loudness on/off, paging on/off per zone) can be configured and secured by the installer.

TECHNICAL SPECIFICATIONS

RMS output power 4 ohms in watts	2 x 80	dynamic output power 8 ohms in watts	100
RMS output power 8 ohms in watts	2 x 60	minimum impedance load per channel in ohms	4
power consumption (max) in watts	< 200	19" (483 mm wide) rack mounting	yes
depth (incl front) in mm	314	power supply	230 VAC
line input unbalanced	4	cooling system	convection
applicable low impedance	yes	Net weight product (kg)	6.60